

Technical Details Speedster and Speedster fs

	Speedster	Speedster fs 20	Speedster fs 26
frame:	ST 52, handlebar ALU	ST 52, handlebar ALU	ST 52, handlebar ALU
Wheels:	v=18 inch, h=20 inch	v=18 inch, h=20 inch	v=18 inch, h=26 inch
Seat angle	26°-36°	26°-36°	26°-36°
length	1,80 m - 2,05 m	1,80 m - 2,05 m	1,80 m - 2,05 m
Seat high:	26 cm -27,5 cm	32 cm -33,5 cm	32 cm -33,5 cm
Middle high of the BB section:	58 cm - 62 cm	58 cm - 62 cm	58 cm - 62 cm
Wheels base:	1,08 m	1,08 m	1,18 m
Suspension:	unsuspended	f = 60 mm, b= 75 mm	f=60 mm, b: 80 mm
Disc brake:	Mech Disc Brakes AVID BB7	Mech Disc Brakes AVID BB7	Mech Disc Brakes AVID BB7
Gears:	Shi 105 triple, 18 Gg with gripshift	Shimano Deore 24 Gg. with Shi gripshift or 27-81 Gg. with Microshift bar end shifters	Shimano Deore 24 Gg. with Shi gripshift or 27-81 Gg. with Microshift bar end shifters
weight :	ca 12,8 kg	ca 17,9 kg	ca 17,9 kg