

Technical Details Wild One

	Wild One 18/20	Wild One 20/20	Wild One 18/26	Wild One 20/26	Wild One 18/29 oder 20/29	Deep Forrest 24/29
Frame::	ST 52, BB section and handlebar ALU	ST 52, BB section and handlebar ALU	ST 52, BB section and handlebar ALU	ST 52, BB section and handlebar ALU	ST 52, Tretlagermast, Lenker aus Alu	ST 52, Tretlagermast, Lenker aus Alu
Wheels:	f=18 inch, b=20 inch	f=20 inch, b=20 inch	f=18 inch, b=26 inch	f=20 inch, b=26 inch	f=20 Zoll, b=26 Zoll	f=24 Zoll, b=29 Zoll
Seat angle:	35 ° - 45 °	35 ° - 45 °	35 ° - 45 °	35 ° - 45 °	35 ° - 45 °	35 ° - 45 °
Narrow track:	79 cm	79 cm	79 cm	79 cm	79 cm	83 cm
Width:	83 cm	83 cm	83 cm	83 cm	83 cm	87 cm
Lenght:	1,80 m - 2,05 m	1,80 m - 2,05 m	1,95 m - 2,20 m	1,95 m - 2,20 m	1,95 m - 2,22 m	1,95 m - 2,22 m
Seat high:	22 cm	25 cm	22 cm	25 cm	22 cm oder 25 cm	32 cm
Middle high of the BB	22 cm - 28 cm	22 cm - 28 cm	22 cm - 28 cm	22 cm - 28 cm	22 cm . 28 cm	
Suspension:	DNM DV 22	DNM DV 22	DNM DV 22	DNM DV 22	DNM DV 22	DNM DV 22
Suspension way:	f=100 mm, b= 80 mm	f=100 mm, b= 80 mm	f=100 mm, b= 80 mm	f=100 mm, b= 80 mm	f: 100 mm b: 110 mm	f: 110 cm b: 110 cm
Wheelbase:	105 cm-108 cm	105 cm-108 cm	114 cm . 118 cm	114 cm . 118 cm	118 cm . 122 cm	1 18 cm . 122 cm
Turning circle:	4,60 m (außen-außen)	4,60 m (außen-außen)	4,90 m (außen-außen)	4,90 m (außen-außen)	4,90 m (außen-außen)	4,90 m (außen-außen)
Disc brake:	Disc Brakes AVID BB7	Disc Brakes AVID BB7	Disc Brakes AVID BB7	Disc Brakes AVID BB7	Disc Brakes AVID BB7	Disc Brakes AVID BB7
gears :	Shim. Deore 24 Gg. or 27-81 Gg. with Microshift bar end shifters	Shim. Deore 24 Gg. or 27-81 Gg. with Microshift bar end shifters	Shim. Deore 24 Gg. or 27-81 Gg. with Microshift bar end shifters	Shim. Deore 24 Gg. or 27-81 Gg. with Microshift bar end shifters	Shim. Deore 24 Gg. or 27-81 Gg. with Microshift bar end shifters	Shim. Deore 24 Gg. or 27-81 Gg. with Microshift bar end shifters
Capacity:	120 kg driver 40 kg carrier	120 kg driver 40 kg carrier	120 kg driver 20 kg carrier	120 kg driver, 20 kg carrier	120 kg driver, 20 kg carrier	120 kg driver, 20 kg carrier
Weight:	Basis: 17,65 kg; with TSwiss Öl-air damper and Carbonparts: 16,65 kg	Basis: 17,65 kg; with DTSwiss Öl-air damper and Carbonparts 16,65 kg	Basis: 17,65 kg; with DTSwiss Öl-air damper and Carbonparts: 16,65 kg	Basis: 17,65 kg; with Swiss Öl-air damper and Carbonparts: 16,65 kg	Basis: 17,9kg mit DTSwiss Öl/Luftdämpfer und Carbon-elementen: 16,9 kg	Basis: 17,9kg mit DTSwiss Öl/Luftdämpfer und Carbonelementen: 16,9 kg